

[Home](#) ▶ [Equipment](#) ▶ [Loaders](#) ▶ [Skid-Steer Loaders](#) ▶ [Non-Current Models](#) ▶ [S130](#)

S130 Skid-Steer Loader

[Shop Parts, Fluids & More](#)

[Service Schedules](#)

[Order Manuals](#)

[Operator Training](#)

[Used Inventory](#)

S130 Specifications

	S130	S130 Skid Steer Loader (2005)	S130
S130 Key Specifications			
Horsepower	34.3 kW	34.3 kW	34.3 kW
Rated Operating Capacity (ISO)	590 kg	590 kg	590 kg
Operating Weight	2297 kg	2150 kg	2375 kg
Auxiliary Std Flow	64 l/min		64 l/min
Joystick Control	Not Applicable	Not Applicable	Optional
Engine			
Engine Cooling	Liquid	Liquid	Liquid
Engine Fuel	Diesel	Diesel	Diesel
Horsepower	34.3 kW	34.3 kW	34.3 kW
Turbocharged Engine	no	N/A	no
Emissions Tier (EPA)			Tier 2
Performance			
Rated Operating Capacity (ISO)	590 kg	590 kg	590 kg

Tipping Load	1245 kg	1179 kg	1195 kg
Operating Weight	2297 kg	2150 kg	2375 kg
Travel Speed	11.7 km/h	11.7 km/h	11.7 km/h

Capacities

Fuel Tank	50.3 l	53 l	50.3 l
-----------	--------	------	--------

Hydraulic System

System Relief @ Quick Couplers	216.15 bar	172.37 bar	182.71 bar
Auxiliary Std Flow	64 l/min		64 l/min

Dimension

Length	3152 mm	3061 mm	2433 mm
Length without Attachment	2433 mm	2446 mm	2433 mm
Length with Standard Bucket	3152 mm	3061 mm	3152 mm
Width	1491 mm	1524 mm	1491 mm
Width (with bucket)	1575 mm	1575 mm	1575 mm
Height	1963 mm	1956 mm	1963 mm
Height with Operator Cab	1963 mm	1956 mm	1963 mm
Height to Bucket Hinge Pin	2781 mm	2771 mm	2781 mm
Reach @ Maximum Height	574 mm	485 mm	574 mm
Turning Radius	1745 mm	1760 mm	1745 mm
Wheelbase	902 mm	902 mm	902 mm

Features

Joystick Control	Not Applicable	Not Applicable	Optional
Air Conditioning	Not Applicable	Not Applicable	Not Applicable

Adjustable Seat	Standard	Standard	Standard
BICS System (Interlock)	Standard	Standard	Standard
Cab Enclosure	Optional	Optional	Optional
Sound Option	Optional	Optional	Optional
Cab Heater	Optional	Optional	Optional
Rear Window	Standard	Standard	Standard
Lift-Arm Support	Standard	Standard	Standard
Suspension Seat	Optional	Optional	Optional
Two Speed Travel	Not Applicable	Not Applicable	Not Applicable
Deluxe Instrumentation	Optional	Optional	Optional
Engine Shutdown	Standard	Standard	Standard
Hydraulic Bucket Positioning	Optional	Optional	Optional
High Flow Option	Not Applicable		Not Applicable
Auxiliary Hydraulics	Standard	Standard	Standard
Bob-Tach Attachment System	Standard	Standard	Standard
Power Bob-Tach	Optional		Optional
Ride Control	Not Applicable		Optional

Search for Parts

Q

Search by Serial Number, Part Number or Keyword

Search ↗



WARNING: This product can expose you to chemicals including engine exhaust (including diesel engine exhaust when equipped), lead and lead compounds, mineral oils, soots, phthalates, and carbon monoxide which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. ~~Specification(s) for some individual equipment will vary based on model variations in design, manufacturing, operating conditions and other factors.~~

Overall, how satisfied are you with the Non-Current model pages on Bobcat.com?

1

2

3

4

5